

Specification Sheet: Dimmable DEPLVED T5 H.O. LED Tube

Retrofitting Is Easy with Our Energy-Efficient LED Tubes

Our DEPLVED T5 H.O. LED Tube Lamps offer a simple, dimmable, energy-efficient solution for outdated T5 H.O. fluorescent lighting. Each two-tube LED lamp kit comes with a matched driver customized to the LED tubes. Just swap out your fluorescent ballast and tubes with our LED driver and tubes, and start saving energy and money. These lightweight T5 H.O. LED tube lamps can decrease your energy usage by 45% or more.

The 0-10V dimmable external driver is designed to operate on input voltages from 120VAC to 277VAC and supplies a safe, low-voltage output to each double-end-power (DEP) T5 H.O. lamp. With an industry-leading rated lifetime of 50,000 hours, these DEPLVED T5 H.O. lamps are also backed by a 5-year warranty.

APPLICATIONS


- Offices & Commercial Buildings
- Big-Box Retail Settings
- Hotels
- Schools
- Hospitals
- Warehouses
- Assisted Living Facilities
- Parking Garages
- Recreation Centers

ILLUMINATION ANGLE



Revolution Lighting Light Distribution

CAN DECREASE ENERGY USAGE BY



vs. Similar Fluorescent Lamps

WARRANTY



Our Industry-Leading 5-Year Limited Warranty Guarantees Unsurpassed Quality

PRODUCT BENEFITS

OPERATIONAL

- 3X greater lamp life than fluorescent
- 50,000-hour lamp life reduces long-term maintenance costs
- Instant on, no warm-up time
- 0-10V dimmable external driver

SAFETY

- Slim, sleek, frosted-glass
- Negligible light depreciation over time
- Superior light output

SUSTAINABILITY

- Lack of UV or IR minimizes concerns with fading or discoloration
- Mercury-free, allowing for non-hazardous disposal
- 100% recyclable



ORDER LOGIC (Ex. DEPLV-T5-58-F-40-2)

Product Description	Lamp Type	Rated Watts	Lens	CCT (K Temp)	Tube No.
DEPLVED = Double-End-Power, Low-Voltage, Ext. Driver	T5 = T5	58 = 58W	F = Frosted Glass	40 = 4000K	2 = 2 Tubes



Specification Sheet: Dimmable DEPLVED T5 H.O. LED Tube

TECHNICAL DATA (Subject to change.)

Catalog No.	Product SKU No.	Rated Watts (per kit)	Lens	Base	Input Voltage (VAC)	Color Temp (K)	Rated Lumens (per kit)	Rated Efficacy (lm/W)	CRI	Illumination Angle	Rated Life (Hours)	Operating Temp. (°F)
56W Low-Voltage Double-End-Power External-Driver H.O. T5 LED Tube, Two-Tube												
DEPLVED-T5-58-F-40-2	204481-113	58 (Kit: 29 x 2)	Glass	G5	120-277	4000	7,000 (Kit: 3,500 x 2)	120	80	308	50,000	-4 to 113

Product is DLC listed.

PHYSICAL DATA

Product Description	Dimensions (in.) *	Weight (lb) *	Lens
Low-Voltage, Double-End-Power External-Driver T5 H.O. Tube Lamp	45.8L x 0.63 Dia.	0.25	Frosted Glass

Note: Product dimensions and weights are for individual LED tube lamps, only.