

# Specification Sheet: ecovista G<sup>2</sup> Billboard Light Fixture

## Put Your Billboard in the Best Light

From edge to edge, your billboard display is brighter, truer and more uniformly illuminated with the energy-efficient ecovista G<sup>2</sup> LED lighting system from Revolution Lighting.

Compared with conventional lighting fixtures, ecovista G<sup>2</sup> provides superior color rendering, with a neutral white daylight and more accurate hue across the display. The ecovista G<sup>2</sup> is extremely focused as 87% of the light produced illuminates the display. Thus, far less light escapes into the night, making the ecovista G<sup>2</sup> a community-friendly technology for Dark Skies initiatives.

Measured against other leading lighting systems, ecovista G<sup>2</sup> consumes up to 86% less energy, making it a good environmental neighbor. With its superior thermal management technology, the ecovista G<sup>2</sup> operates cooler, thus it will last longer than competing products before requiring replacement.

### APPLICATIONS


- Billboards
- Signs

### NEMA TYPE



Revolution Lighting  
Light Distribution

### CAN DECREASE ENERGY USAGE BY



vs. Similar  
Fixtures

### WARRANTY



7-year fixture/LED Limited  
Warranty and 5-Year Power Supply  
Limited Warranty Guarantees  
Unsurpassed Quality

## PRODUCT BENEFITS

### OPERATIONAL

- 3X greater lamp life than fluorescent
- 100,000-hour lamp life
- Instant on, no warm-up time
- Utilizes Total Internal Reflective (TIR) optics to ensure long-life clarity/optical performance

### SAFETY

- No glass
- RoHS compliant
- ETL electrical safety listing

### SUSTAINABILITY

- Inhibitors in optics and finish
- Mercury-free, allowing for non-hazardous disposal
- 100% recyclable (excluding power supply)



**LUMi**efficient™

# Specification Sheet: ecovista G<sup>2</sup> Billboard Light Fixture

## TECHNICAL DATA (Subject to change.)

Product SKU No.	Lamp Wattage (W)	LEDs per Fixture	Max to Min Ratio (14 x 48)	Avg to Min Ratio (14 x 48)	Operating Current (Amps)	Input Voltage (VAC)	Color Temp (K)	Lumens	Efficacy (lm/W)	CRI	NEMA Type	Rated Life (Hours)	Operating Temp. (°F)
<b>ecovista G2 Billboard Wall Washer 3' Billboard/Wall Washer/Flood</b>													
EVG236	124	20	2.64:1	1:80:1	1.8	120-277	4200	11,530	94	82	7H x 7V	100,000	-40 to 131
<b>ecovista G2 Billboard Wall Washer EV Wall Mount</b>													
3350016901													
<b>ecovista G2 Billboard Wall Washer EV Ground Mount</b>													
9100001501													



Total Internal Reflective (TIR) optics are used to achieve even distribution of light.

## SHIPPING DATA (Subject to change)

Product SKU No.	Nominal Length (ft)	Product Dimensions (in.)	Product Weight (lb)
<b>ecovista G2 Billboard Wall Washer 3' Billboard/Wall Washer/Flood</b>			
EVG236	3	36.25L x 4W x 5.75H	13.8