

# Specification Sheet: G2 EZ-Fit DEP T8 LED Tube Lamp

## The Energy Efficient LED Solution

Revolution Lighting's High-Performance T8 DEP LED Tubes can reduce your lighting energy use by as much as 55% compared to fluorescent lights and provide a superior quality of light.

These high-efficiency, UL Type-B double-end-powered tube lamps have a lightweight plastic lens for smooth, even illumination and are backed with our industry-leading 50,000-hour lamp life and 5-year warranty.

See order logic table below for our TAA-compliant products. Contact your Revolution Lighting representative for pricing and more information.

### APPLICATIONS


- Offices & Commercial Buildings
- Big-Box Retail Outlets
- Hotels
- Schools
- Hospitals
- Warehouses
- Assisted Living Facilities
- Recreation Centers

### ILLUMINATION ANGLE



Revolution Lighting Light Distribution

### CAN DECREASE ENERGY USAGE BY



vs. Similar Fluorescent Lamps

### WARRANTY



Our Industry-Leading 5-Year Limited Warranty Guarantees Unsurpassed Quality

## PRODUCT BENEFITS

### OPERATIONAL

- 3X greater lamp life than fluorescent
- Supported by industry-leading 5-year warranty
- 50,000-hour lamp life reduces long-term maintenance costs
- Instant on, no warm-up time

### SAFETY

- No glass
- Negligible light depreciation over time
- Seamless, lightweight plastic tube
- Complies with UL 1598C and UL 1993
- Suitable for use in dry and damp locations

### SUSTAINABILITY

- Lack of UV or minimizes concerns with fading or discoloration
- No buzzing
- Mercury-free, allowing for non-hazardous disposal
- 100% recyclable



## ORDER LOGIC (Ex. G2EZFDEP-48-15-FP-35 or G2EZFDEP-48-15-FP-35-A))

Product Description	Length (in.)	Wattage	Lens	CCT (K Temp)	TAA
G2EZFDEP = G2 EZ-Fit DEP T8 LED Tube Lamp	- 24 = 2 ft (24 in.)	- 9 = 9W	FP = Frosted Plastic	30 = 3000K	Blank = Standard (no TAA) A = TAA (Trade Agreements Act)
	- 36 = 3 ft (36 in.)	- 12 = 12W		35 = 3500K	
		10.5 = 10.5W		40 = 4000K	
	- 48 = 4 ft (48 in.)	- 15 = 15W		50 = 5000K	
		18 = 18W			



# Specification Sheet: G2 EZ-Fit DEP T8 LED Tube Lamp

## TECHNICAL DATA (Subject to change)

Catalog No.	Product SKU No.*	TAA Option*	Rated Watts	Base	Lens	Color Temp (K) †	Input Voltage (VAC)	Rated Lumens	Rated Efficacy (lm/W)	CRI	Illumination Angle (°)	Rated Life (Hours)	Operating Temp. (°F)
<b>9W 2-FT G2 EZ-Fit DEP Plastic T8 LED Tube Lamp</b>													
G2EZFDEP-24-9-FP-30	202010-211	Yes	9.6	G13	Frosted	3000	120-277	1,127	117	82	312	55,000	-4 to 113
G2EZFDEP-24-9-FP-35	202010-212	Yes	9.6	G13	Frosted	3500	120-277	1,143	119	82	312	55,000	-4 to 113
G2EZFDEP-24-9-FP-40	202010-213	Yes	9.6	G13	Frosted	4000	120-277	1,158	121	82	312	55,000	-4 to 113
G2EZFDEP-24-9-FP-50	202010-215	Yes	9.6	G13	Frosted	5000	120-277	1,189	124	82	312	55,000	-4 to 113
<b>12W 3-FT G2 EZ-Fit DEP Plastic T8 LED Tube Lamp</b>													
G2EZFDEP-36-12-FP-30	203012-211	Yes	13	G13	Frosted	3000	120-277	1,486	114	82	312	55,000	-4 to 113
G2EZFDEP-36-12-FP-35	203012-212	Yes	13	G13	Frosted	3500	120-277	1,509	115	82	312	55,000	-4 to 113
G2EZFDEP-36-12-FP-40	203012-213	Yes	13	G13	Frosted	4000	120-277	1,532	117	82	312	55,000	-4 to 113
G2EZFDEP-36-12-FP-50	203012-215	Yes	13.1	G13	Frosted	5000	120-277	1,578	120	83	312	55,000	-4 to 113
<b>10.5W 4-FT G2 EZ-Fit DEP Plastic T8 LED Tube Lamp</b>													
G2EZFDEP-48-10.5-FP-30	204011-211	Yes	10.8	G13	Frosted	3000	120-277	1,670	155	84	312	55,000	-4 to 113
G2EZFDEP-48-10.5-FP-35	204011-212	Yes	10.8	G13	Frosted	3500	120-277	1,679	155	84	312	55,000	-4 to 113
G2EZFDEP-48-10.5-FP-40	204011-213	Yes	10.8	G13	Frosted	4000	120-277	1,688	156	84	312	55,000	-4 to 113
G2EZFDEP-48-10.5-FP-50	204011-215	Yes	10.8	G13	Frosted	5000	120-277	1,705	157	84	312	55,000	-4 to 113
<b>15W 4-FT G2 EZ-Fit DEP Plastic T8 LED Tube Lamp</b>													
G2EZFDEP-48-15-FP-30	204014-211	Yes	16.2	G13	Frosted	3000	120-277	2,260	139	82	312	55,000	-4 to 113
G2EZFDEP-48-15-FP-35	204014-212	Yes	16.3	G13	Frosted	3500	120-277	2,278	139	82	312	55,000	-4 to 113
G2EZFDEP-48-15-FP-40	204014-213	Yes	16.3	G13	Frosted	4000	120-277	2,295	140	82	312	55,000	-4 to 113
G2EZFDEP-48-15-FP-50	204014-215	Yes	16.3	G13	Frosted	5000	120-277	2,330	142	84	312	55,000	-4 to 113
<b>18W 4-FT EZ-Fit G2 DEP Plastic T8 LED Tube Lamp</b>													
G2EZFDEP-48-18-FP-30	204015-211	Yes	18.6	G13	Frosted	3000	120-277	2,487	133	83	312	55,000	-4 to 113
G2EZFDEP-48-18-FP-35	204015-212	Yes	18.6	G13	Frosted	3500	120-277	2,520	135	83	312	55,000	-4 to 113
G2EZFDEP-48-18-FP-40	204015-213	Yes	18.6	G13	Frosted	4000	120-277	2,553	137	83	312	55,000	-4 to 113
G2EZFDEP-48-18-FP-50	204015-215	Yes	18.7	G13	Frosted	5000	120-277	2,618	140	83	312	55,000	-4 to 113

Product is DLC listed.

\* Note: When ordering TAA-Compliant tubes, include the extension "-A" after the SKU No., as done in the Order Logic table. Example: 204011-213-A

## PHYSICAL DATA

Catalog No.	Product SKU No.	Product Dimensions (in.)	Product Weight (lb)
<b>9W 2-FT G2 EZ-Fit DEP T8 LED Nano Tube Lamp</b>			
G2EZFDEP-24-9-N-30	202010-211	24L x 1 Dia.	0.15
G2EZFDEP-24-9-N-35	202010-212	24L x 1 Dia.	0.15
G2EZFDEP-24-9-N-40	202010-213	24L x 1 Dia.	0.15
G2EZFDEP-24-9-N-50	202010-215	24L x 1 Dia.	0.15
<b>12W 3-FT G2 EZ-Fit DEP T8 LED Nano Tube Lamp</b>			
G2EZFDEP-36-12-N-30	203012-211	36L x 1 Dia.	0.22
G2EZFDEP-36-12-N-35	203012-212	36L x 1 Dia.	0.22
G2EZFDEP-36-12-N-40	203012-213	36L x 1 Dia.	0.22
G2EZFDEP-36-12-N-50	203012-215	36L x 1 Dia.	0.22
<b>10.5W 4-FT G2 EZ-Fit DEP T8 LED Nano Tube Lamp</b>			
G2EZFDEP-48-10.5-N-30	204011-211	48L x 1 Dia.	0.29
G2EZFDEP-48-10.5-N-35	204011-212	48L x 1 Dia.	0.29
G2EZFDEP-48-10.5-N-40	204011-213	48L x 1 Dia.	0.29
G2EZFDEP-48-10.5-N-50	204011-215	48L x 1 Dia.	0.29
<b>15W 4-FT G2 EZ-Fit DEP T8 LED Nano Tube Lamp</b>			
G2EZFDEP-48-15-N-30	204014-211	48L x 1 Dia.	0.29
G2EZFDEP-48-15-N-35	204014-212	48L x 1 Dia.	0.29
G2EZFDEP-48-15-N-40	204014-213	48L x 1 Dia.	0.29
G2EZFDEP-48-15-N-50	204014-215	48L x 1 Dia.	0.29
<b>18W 4-FT G2 EZ-Fit DEP T8 LED Nano Tube Lamp</b>			
G2EZFDEP-48-18-N-30	204015-211	48L x 1 Dia.	0.29
G2EZFDEP-48-18-N-35	204015-212	48L x 1 Dia.	0.29
G2EZFDEP-48-18-N-40	204015-213	48L x 1 Dia.	0.29
G2EZFDEP-48-18-N-50	204015-215	48L x 1 Dia.	0.29