

Specification Sheet: G2 Eco Linear High Bays

Increase Visibility with Brighter, More Efficient Lighting

Better lighting can reduce eye fatigue, improve visibility, and transform the appeal of a space, from warehouses and gymnasiums to big-box stores and recreation centers. Our G2 Eco Linear High Bay fixtures provide bright, symmetrical lighting and minimal glare.


Designed for easy mounting (V-hook, surface, cable (optional), or pendant (optional) mount), these strong, lightweight, fully-assembled fixtures replace existing fluorescent or MH high-bays and provide superior lighting uniformity for high visibility. The ultra-high efficiency of our G2 Eco Linear High Bays reduces energy consumption by 60% over existing linear fluorescent fixtures with the same light output, increasing the return on your lighting investment.

With standard 0-10V dimming and optional integrated microwave motion sensors, our G2 Eco Linear High Bays can reduce energy costs even further. What's more, with a 50,000-hour rated life and 7-year warranty, these fixtures significantly reduce your long-term operational and maintenance costs.

APPLICATIONS

- Warehouses
- Recreation Centers
- Gymnasiums
- Big-Box Stores
- Indoor Stadiums

BEAM ANGLE



Revolution Lighting Light Distribution

CAN DECREASE ENERGY USAGE BY



vs. Similar Fluorescent Lamps

WARRANTY



Our Industry-Leading 7-Year Limited Warranty Guarantees Unsurpassed Quality



2ft Eco Linear High Bay
55W / 81W / 101W



2ft Eco Linear High Bay
141W / 161W / 201W



2ft Eco Linear High Bay
181W



4ft Eco Linear High Bay
141W / 201W



4ft Eco Linear High Bay
281W / 321W



4ft Eco Linear High Bay
481W

PRODUCT BENEFITS

OPERATIONAL

- Ultra-high 150lm/W lighting efficiency
- 0-10V dimming
- 50,000-hour rated lifetime
- Minimal maintenance
- Supported by 7-year warranty
- V-hook-hanging and surface-mounting included standard

AVAILABLE OPTIONS AND ACCESSORIES:

- Multiple optical options
- Pendant-mounting bracket and 12ft aircraft cable hanging kits
- Factory-installed integrated microwave motion sensor
- Factory-installed integrated battery backup unit
- External PIR dimmable sensor (for field installation)
- Handheld remote control unit compatible with both integrated microwave motion and external PIR dimmable sensors
- Wire guards for all fixture sizes
- Factory-installed 10KA surge protector

ORDER LOGIC (Ex. G2ELHB-2-81-SV-DLM-40-D-IS-BB)

Product Description	Length	Power	Input Voltages (VAC)	Lens	CCT (K Temp)	Dimming	Sensor Option	Battery Backup Option
G2ELHB = G2 Eco Linear High Bay	2 = 2 ft	55 = 55W	SV = 120-277	DLA = Discrete Lens Aisle	40 = 4000K	D = 0-10V Dimming ¹	Blank = No Sensor IS = Integrated Microwave Sensor ²	Blank = No Battery Backup BB = Integrated Battery Backup ^{2,3}
		81 = 81W		DLM = Discrete Lens Medium				
	4 = 4 ft	141 = 141W	SV = 120-277	DLA = Discrete Lens Aisle	40 = 4000K	D = 0-10V Dimming ¹	Blank = No Sensor IS = Integrated Microwave Sensor ²	Blank = No Battery Backup BB = Integrated Battery Backup ^{2,3}
		201 = 201W		DLM = Discrete Lens Medium				
		281 = 281W		PL = Prismatic Lens				
		321 = 321W						
		481 = 481W						

¹: All models are offered with 0-10VDC dimming functionality.

²: Integrated sensor and integrated battery-backup options can be special ordered, subject to MOQs. Please contact your Revolution Lighting distributor for more information on pricing and availability.

³: The battery-backup option requires a reduced maximum ambient operating temperature of 122 °F.



Specification Sheet: G2 Eco Linear High Bays

TECHNICAL DATA (Subject to change. See footnotes and chart below for product configuration information.)

Catalog No.*	Product SKU No.*	Rated Watts	Lens	Mounting	Input Voltage (VAC)	Color Temp (K)	Rated Lumens	Rated Efficacy (lm/W)	CRI	Rated Lifetime (Hours)	Operating Temp. (°F)
2-ft 55W G2 Eco Linear High Bay, Standard Voltage											
G2ELHB-2-55-SV-XXX-30-D	128010-3X1	55	See Legend	V-hook	120-277	3000	8,332	151	80	50,000	-4 to 131
G2ELHB-2-55-SV-XXX-40-D	128010-3X3	55	See Legend	V-hook	120-277	4000	8,624	156	80	50,000	-4 to 131
G2ELHB-2-55-SV-XXX-50-D	128010-3X5	55	See Legend	V-hook	120-277	5000	8,717	158	80	50,000	-4 to 131
2-ft 55W G2 Eco Linear High Bay, Standard Voltage, Integrated Microwave Sensor											
G2ELHB-2-55-SV-XXX-30-D-IS	128020-3X1	55	See Legend	V-hook	120-277	3000	8,332	151	80	50,000	-4 to 131
G2ELHB-2-55-SV-XXX-40-D-IS	128020-3X3	55	See Legend	V-hook	120-277	4000	8,624	156	80	50,000	-4 to 131
G2ELHB-2-55-SV-XXX-50-D-IS	128020-3X5	55	See Legend	V-hook	120-277	5000	8,717	158	80	50,000	-4 to 131
2-ft 55W G2 Eco Linear High Bay, Standard Voltage, 16W Battery Backup											
G2ELHB-2-55-SV-XXX-30-D-BB	128310-3X1	55	See Legend	V-hook	120-277	3000	8,332	151	80	50,000	-4 to 122
G2ELHB-2-55-SV-XXX-40-D-BB	128310-3X3	55	See Legend	V-hook	120-277	4000	8,624	156	80	50,000	-4 to 122
G2ELHB-2-55-SV-XXX-50-D-BB	128310-3X5	55	See Legend	V-hook	120-277	5000	8,717	158	80	50,000	-4 to 122
2-ft 55W G2 Eco Linear High Bay, Standard Voltage, Integrated Microwave Sensor, 16W Battery Backup											
G2ELHB-2-55-SV-XXX-30-D-IS-BB	128320-3X1	55	See Legend	V-hook	120-277	3000	8,332	151	80	50,000	-4 to 122
G2ELHB-2-55-SV-XXX-40-D-IS-BB	128320-3X3	55	See Legend	V-hook	120-277	4000	8,624	156	80	50,000	-4 to 122
G2ELHB-2-55-SV-XXX-50-D-IS-BB	128320-3X5	55	See Legend	V-hook	120-277	5000	8,717	158	80	50,000	-4 to 122
2-ft 81W G2 Eco Linear High Bay, Standard Voltage											
G2ELHB-2-81-SV-XXX-30-D	128011-3X1	81	See Legend	V-hook	120-277	3000	11,753	145	80	50,000	-4 to 131
G2ELHB-2-81-SV-XXX-40-D	128011-3X3	81	See Legend	V-hook	120-277	4000	12,158	150	80	50,000	-4 to 131
G2ELHB-2-81-SV-XXX-50-D	128011-3X5	81	See Legend	V-hook	120-277	5000	12,287	151	80	50,000	-4 to 131
2-ft 81W G2 Eco Linear High Bay, Standard Voltage, Integrated Microwave Sensor											
G2ELHB-2-81-SV-XXX-30-D-IS	128021-3X1	81	See Legend	V-hook	120-277	3000	11,753	145	80	50,000	-4 to 131
G2ELHB-2-81-SV-XXX-40-D-IS	128021-3X3	81	See Legend	V-hook	120-277	4000	12,158	150	80	50,000	-4 to 131
G2ELHB-2-81-SV-XXX-50-D-IS	128021-3X5	81	See Legend	V-hook	120-277	5000	12,287	151	80	50,000	-4 to 131
2-ft 81W G2 Eco Linear High Bay, Standard Voltage, 16W Battery Backup											
G2ELHB-2-81-SV-XXX-30-D-BB	128311-3X1	81	See Legend	V-hook	120-277	3000	11,753	145	80	50,000	-4 to 122
G2ELHB-2-81-SV-XXX-40-D-BB	128311-3X3	81	See Legend	V-hook	120-277	4000	12,158	150	80	50,000	-4 to 122
G2ELHB-2-81-SV-XXX-50-D-BB	128311-3X5	81	See Legend	V-hook	120-277	5000	12,287	151	80	50,000	-4 to 122
2-ft 81W G2 Eco Linear High Bay, Standard Voltage, Integrated Microwave Sensor, 16W Battery Backup											
G2ELHB-2-81-SV-XXX-30-D-IS-BB	128321-3X1	81	See Legend	V-hook	120-277	3000	11,753	145	80	50,000	-4 to 122
G2ELHB-2-81-SV-XXX-40-D-IS-BB	128321-3X3	81	See Legend	V-hook	120-277	4000	12,158	150	80	50,000	-4 to 122
G2ELHB-2-81-SV-XXX-50-D-IS-BB	128321-3X5	81	See Legend	V-hook	120-277	5000	12,287	151	80	50,000	-4 to 122
2-ft 101W G2 Eco Linear High Bay, Standard Voltage											
G2ELHB-2-101-SV-XXX-30-D	128012-3X1	101	See Legend	V-hook	120-277	3000	14,605	144	80	50,000	-4 to 131
G2ELHB-2-101-SV-XXX-40-D	128012-3X3	101	See Legend	V-hook	120-277	4000	15,119	149	80	50,000	-4 to 131
G2ELHB-2-101-SV-XXX-50-D	128012-3X5	101	See Legend	V-hook	120-277	5000	15,291	151	80	50,000	-4 to 131
2-ft 101W G2 Eco Linear High Bay, Standard Voltage, Integrated Microwave Sensor											
G2ELHB-2-101-SV-XXX-30-D-IS	128022-3X1	101	See Legend	V-hook	120-277	3000	14,605	144	80	50,000	-4 to 131
G2ELHB-2-101-SV-XXX-40-D-IS	128022-3X3	101	See Legend	V-hook	120-277	4000	15,119	149	80	50,000	-4 to 131
G2ELHB-2-101-SV-XXX-50-D-IS	128022-3X5	101	See Legend	V-hook	120-277	5000	15,291	151	80	50,000	-4 to 131
2-ft 101W G2 Eco Linear High Bay, Standard Voltage, 16W Battery Backup											
G2ELHB-2-101-SV-XXX-30-D-BB	128312-3X1	101	See Legend	V-hook	120-277	3000	14,605	144	80	50,000	-4 to 122
G2ELHB-2-101-SV-XXX-40-D-BB	128312-3X3	101	See Legend	V-hook	120-277	4000	15,119	149	80	50,000	-4 to 122
G2ELHB-2-101-SV-XXX-50-D-BB	128312-3X5	101	See Legend	V-hook	120-277	5000	15,291	151	80	50,000	-4 to 122
2-ft 101W G2 Eco Linear High Bay, Standard Voltage, Integrated Microwave Sensor, 16W Battery Backup											
G2ELHB-2-101-SV-XXX-30-D-IS-BB	128322-3X1	101	See Legend	V-hook	120-277	3000	14,605	144	80	50,000	-4 to 122
G2ELHB-2-101-SV-XXX-40-D-IS-BB	128322-3X3	101	See Legend	V-hook	120-277	4000	15,119	149	80	50,000	-4 to 122
G2ELHB-2-101-SV-XXX-50-D-IS-BB	128322-3X5	101	See Legend	V-hook	120-277	5000	15,291	151	80	50,000	-4 to 122
2-ft 141W G2 Eco Linear High Bay, Standard Voltage											
G2ELHB-2-141-SV-XXX-30-D	128013-3X1	141	See Legend	V-hook	120-277	3000	20,698	146	80	50,000	-4 to 131
G2ELHB-2-141-SV-XXX-40-D	128013-3X3	141	See Legend	V-hook	120-277	4000	21,403	151	80	50,000	-4 to 131
G2ELHB-2-141-SV-XXX-50-D	128013-3X5	141	See Legend	V-hook	120-277	5000	21,643	153	80	50,000	-4 to 131
2-ft 141W G2 Eco Linear High Bay, Standard Voltage, Integrated Microwave Sensor											
G2ELHB-2-141-SV-XXX-30-D-IS	128023-3X1	141	See Legend	V-hook	120-277	3000	20,698	146	80	50,000	-4 to 131
G2ELHB-2-141-SV-XXX-40-D-IS	128023-3X3	141	See Legend	V-hook	120-277	4000	21,403	151	80	50,000	-4 to 131
G2ELHB-2-141-SV-XXX-50-D-IS	128023-3X5	141	See Legend	V-hook	120-277	5000	21,643	153	80	50,000	-4 to 131
2-ft 141W G2 Eco Linear High Bay, Standard Voltage, 16W Battery Backup											
G2ELHB-2-141-SV-XXX-30-D-BB	128313-3X1	141	See Legend	V-hook	120-277	3000	20,698	146	80	50,000	-4 to 122
G2ELHB-2-141-SV-XXX-40-D-BB	128313-3X3	141	See Legend	V-hook	120-277	4000	21,403	151	80	50,000	-4 to 122
G2ELHB-2-141-SV-XXX-50-D-BB	128313-3X5	141	See Legend	V-hook	120-277	5000	21,643	153	80	50,000	-4 to 122
2-ft 141W G2 Eco Linear High Bay, Standard Voltage, Integrated Microwave Sensor, 16W Battery Backup											
G2ELHB-2-141-SV-XXX-30-D-IS-BB	128323-3X1	141	See Legend	V-hook	120-277	3000	20,698	146	80	50,000	-4 to 122
G2ELHB-2-141-SV-XXX-40-D-IS-BB	128323-3X3	141	See Legend	V-hook	120-277	4000	21,403	151	80	50,000	-4 to 122
G2ELHB-2-141-SV-XXX-50-D-IS-BB	128323-3X5	141	See Legend	V-hook	120-277	5000	21,643	153	80	50,000	-4 to 122

Specification Sheet: G2 Eco Linear High Bays

TECHNICAL DATA (Subject to change. See footnotes and chart below for product configuration information.)

Catalog No.*	Product SKU No.*	Rated Watts	Lens	Mounting	Input Voltage (VAC)	Color Temp (K)	Rated Lumens	Rated Efficacy (lm/W)	CRI	Rated Lifetime (Hours)	Operating Temp. (°F)
2-ft 161W G2 Eco Linear High Bay, Standard Voltage											
G2ELHB-2-161-SV-XXX-30-D	128015-3X1	161	See Legend	V-hook	120-277	3000	23,393	145	80	50,000	-4 to 131
G2ELHB-2-161-SV-XXX-40-D	128015-3X3	161	See Legend	V-hook	120-277	4000	24,214	150	80	50,000	-4 to 131
G2ELHB-2-161-SV-XXX-50-D	128015-3X5	161	See Legend	V-hook	120-277	5000	24,488	152	80	50,000	-4 to 131
2-ft 161W G2 Eco Linear High Bay, Standard Voltage, Integrated Microwave Sensor											
G2ELHB-2-161-SV-XXX-30-D-IS	128025-3X1	161	See Legend	V-hook	120-277	3000	23,393	145	80	50,000	-4 to 131
G2ELHB-2-161-SV-XXX-40-D-IS	128025-3X3	161	See Legend	V-hook	120-277	4000	24,214	150	80	50,000	-4 to 131
G2ELHB-2-161-SV-XXX-50-D-IS	128025-3X5	161	See Legend	V-hook	120-277	5000	24,488	152	80	50,000	-4 to 131
2-ft 161W G2 Eco Linear High Bay, Standard Voltage, 16W Battery Backup											
G2ELHB-2-161-SV-XXX-30-D-BB	128315-3X1	161	See Legend	V-hook	120-277	3000	23,393	145	80	50,000	-4 to 122
G2ELHB-2-161-SV-XXX-40-D-BB	128315-3X3	161	See Legend	V-hook	120-277	4000	24,214	150	80	50,000	-4 to 122
G2ELHB-2-161-SV-XXX-50-D-BB	128315-3X5	161	See Legend	V-hook	120-277	5000	24,488	152	80	50,000	-4 to 122
2-ft 161W G2 Eco Linear High Bay, Standard Voltage, Integrated Microwave Sensor, 16W Battery Backup											
G2ELHB-2-161-SV-XXX-30-D-IS-BB	128325-3X1	161	See Legend	V-hook	120-277	3000	23,393	145	80	50,000	-4 to 122
G2ELHB-2-161-SV-XXX-40-D-IS-BB	128325-3X3	161	See Legend	V-hook	120-277	4000	24,214	150	80	50,000	-4 to 122
G2ELHB-2-161-SV-XXX-50-D-IS-BB	128325-3X5	161	See Legend	V-hook	120-277	5000	24,488	152	80	50,000	-4 to 122
2-ft 201W G2 Eco Linear High Bay, Standard Voltage											
G2ELHB-2-201-SV-XXX-30-D	128016-3X1	201	See Legend	V-hook	120-277	3000	28,381	141	80	50,000	-4 to 131
G2ELHB-2-201-SV-XXX-40-D	128016-3X3	201	See Legend	V-hook	120-277	4000	29,788	148	80	50,000	-4 to 131
G2ELHB-2-201-SV-XXX-50-D	128016-3X5	201	See Legend	V-hook	120-277	5000	30,170	150	80	50,000	-4 to 131
2-ft 201W G2 Eco Linear High Bay, Standard Voltage, Integrated Microwave Sensor											
G2ELHB-2-201-SV-XXX-30-D-IS	128026-3X1	201	See Legend	V-hook	120-277	3000	28,381	141	80	50,000	-4 to 131
G2ELHB-2-201-SV-XXX-40-D-IS	128026-3X3	201	See Legend	V-hook	120-277	4000	29,788	148	80	50,000	-4 to 131
G2ELHB-2-201-SV-XXX-50-D-IS	128026-3X5	201	See Legend	V-hook	120-277	5000	30,170	150	80	50,000	-4 to 131
2-ft 201W G2 Eco Linear High Bay, Standard Voltage, 16W Battery Backup											
G2ELHB-2-201-SV-XXX-30-D-BB	128316-3X1	201	See Legend	V-hook	120-277	3000	28,381	141	80	50,000	-4 to 122
G2ELHB-2-201-SV-XXX-40-D-BB	128316-3X3	201	See Legend	V-hook	120-277	4000	29,788	148	80	50,000	-4 to 122
G2ELHB-2-201-SV-XXX-50-D-BB	128316-3X5	201	See Legend	V-hook	120-277	5000	30,170	150	80	50,000	-4 to 122
2-ft 201W G2 Eco Linear High Bay, Standard Voltage, Integrated Microwave Sensor, 16W Battery Backup											
G2ELHB-2-201-SV-XXX-30-D-IS-BB	128326-3X1	201	See Legend	V-hook	120-277	3000	28,381	141	80	50,000	-4 to 122
G2ELHB-2-201-SV-XXX-40-D-IS-BB	128326-3X3	201	See Legend	V-hook	120-277	4000	29,788	148	80	50,000	-4 to 122
G2ELHB-2-201-SV-XXX-50-D-IS-BB	128326-3X5	201	See Legend	V-hook	120-277	5000	30,170	150	80	50,000	-4 to 122
4-ft 141W G2 Eco Linear High Bay, Standard Voltage											
G2ELHB-4-141-SV-XXX-30-D	128014-3X1	141	See Legend	V-hook	120-277	3000	21,150	150	80	50,000	-4 to 131
G2ELHB-4-141-SV-XXX-40-D	128014-3X3	141	See Legend	V-hook	120-277	4000	21,150	150	80	50,000	-4 to 131
G2ELHB-4-141-SV-XXX-50-D	128014-3X5	141	See Legend	V-hook	120-277	5000	21,150	150	80	50,000	-4 to 131
4-ft 141W G2 Eco Linear High Bay, Standard Voltage, Integrated Microwave Sensor											
G2ELHB-4-141-SV-XXX-30-D-IS	128024-3X1	141	See Legend	V-hook	120-277	3000	21,150	150	80	50,000	-4 to 131
G2ELHB-4-141-SV-XXX-40-D-IS	128024-3X3	141	See Legend	V-hook	120-277	4000	21,150	150	80	50,000	-4 to 131
G2ELHB-4-141-SV-XXX-50-D-IS	128024-3X5	141	See Legend	V-hook	120-277	5000	21,150	150	80	50,000	-4 to 131
4-ft 141W G2 Eco Linear High Bay, Standard Voltage, 16W Battery Backup											
G2ELHB-4-141-SV-XXX-30-D-BB	128314-3X1	141	See Legend	V-hook	120-277	3000	21,150	150	80	50,000	-4 to 122
G2ELHB-4-141-SV-XXX-40-D-BB	128314-3X3	141	See Legend	V-hook	120-277	4000	21,150	150	80	50,000	-4 to 122
G2ELHB-4-141-SV-XXX-50-D-BB	128314-3X5	141	See Legend	V-hook	120-277	5000	21,150	150	80	50,000	-4 to 122
4-ft 141W G2 Eco Linear High Bay, Standard Voltage, Integrated Microwave Sensor, 16W Battery Backup											
G2ELHB-4-141-SV-XXX-30-D-IS-BB	128324-3X1	141	See Legend	V-hook	120-277	3000	21,150	150	80	50,000	-4 to 122
G2ELHB-4-141-SV-XXX-40-D-IS-BB	128324-3X3	141	See Legend	V-hook	120-277	4000	21,150	150	80	50,000	-4 to 122
G2ELHB-4-141-SV-XXX-50-D-IS-BB	128324-3X5	141	See Legend	V-hook	120-277	5000	21,150	150	80	50,000	-4 to 122
4-ft 201W G2 Eco Linear High Bay, Standard Voltage											
G2ELHB-4-201-SV-XXX-30-D	128017-3X1	201	See Legend	V-hook	120-277	3000	28,602	142	80	50,000	-4 to 131
G2ELHB-4-201-SV-XXX-40-D	128017-3X3	201	See Legend	V-hook	120-277	4000	29,647	147	80	50,000	-4 to 131
G2ELHB-4-201-SV-XXX-50-D	128017-3X5	201	See Legend	V-hook	120-277	5000	29,989	149	80	50,000	-4 to 131
4-ft 201W G2 Eco Linear High Bay, Standard Voltage, Integrated Microwave Sensor											
G2ELHB-4-201-SV-XXX-30-D-IS	128027-3X1	201	See Legend	V-hook	120-277	3000	28,602	142	80	50,000	-4 to 131
G2ELHB-4-201-SV-XXX-40-D-IS	128027-3X3	201	See Legend	V-hook	120-277	4000	29,647	147	80	50,000	-4 to 131
G2ELHB-4-201-SV-XXX-50-D-IS	128027-3X5	201	See Legend	V-hook	120-277	5000	29,989	149	80	50,000	-4 to 131
4-ft 201W G2 Eco Linear High Bay, Standard Voltage, 16W Battery Backup											
G2ELHB-4-201-SV-XXX-30-D-BB	128317-3X1	201	See Legend	V-hook	120-277	3000	28,602	142	80	50,000	-4 to 122
G2ELHB-4-201-SV-XXX-40-D-BB	128317-3X3	201	See Legend	V-hook	120-277	4000	29,647	147	80	50,000	-4 to 122
G2ELHB-4-201-SV-XXX-50-D-BB	128317-3X5	201	See Legend	V-hook	120-277	5000	29,989	149	80	50,000	-4 to 122
4-ft 201W G2 Eco Linear High Bay, Standard Voltage, Integrated Microwave Sensor, 16W Battery Backup											
G2ELHB-4-201-SV-XXX-30-D-IS-BB	128327-3X1	201	See Legend	V-hook	120-277	3000	28,602	142	80	50,000	-4 to 122
G2ELHB-4-201-SV-XXX-40-D-IS-BB	128327-3X3	201	See Legend	V-hook	120-277	4000	29,647	147	80	50,000	-4 to 122
G2ELHB-4-201-SV-XXX-50-D-IS-BB	128327-3X5	201	See Legend	V-hook	120-277	5000	29,989	149	80	50,000	-4 to 122

Specification Sheet: G2 Eco Linear High Bays

TECHNICAL DATA (Subject to change. See footnotes and chart below for product configuration information.)

Catalog No.*	Product SKU No.*	Rated Watts	Lens	Mounting	Input Voltage (VAC)	Color Temp (K)	Rated Lumens	Rated Efficacy (lm/W)	CRI	Rated Lifetime (Hours)	Operating Temp. (°F)
4-ft 281W G2 Eco Linear High Bay, Standard Voltage											
G2ELHB-4-281-SV-XXX-30-D	128018-3X1	281	See Legend	V-hook	120-277	3000	40,267	143	80	50,000	-4 to 131
G2ELHB-4-281-SV-XXX-40-D	128018-3X3	281	See Legend	V-hook	120-277	4000	42,515	151	80	50,000	-4 to 131
G2ELHB-4-281-SV-XXX-50-D	128018-3X5	281	See Legend	V-hook	120-277	5000	43,077	153	80	50,000	-4 to 131
4-ft 281W G2 Eco Linear High Bay, Standard Voltage, Integrated Microwave Sensor											
G2ELHB-4-281-SV-XXX-30-D-IS	128028-3X1	281	See Legend	V-hook	120-277	3000	40,267	143	80	50,000	-4 to 131
G2ELHB-4-281-SV-XXX-40-D-IS	128028-3X3	281	See Legend	V-hook	120-277	4000	42,515	151	80	50,000	-4 to 131
G2ELHB-4-281-SV-XXX-50-D-IS	128028-3X5	281	See Legend	V-hook	120-277	5000	43,077	153	80	50,000	-4 to 131
4-ft 281W G2 Eco Linear High Bay, Standard Voltage, 16W Battery Backup											
G2ELHB-4-281-SV-XXX-30-D-BB	128318-3X1	281	See Legend	V-hook	120-277	3000	40,267	143	80	50,000	-4 to 122
G2ELHB-4-281-SV-XXX-40-D-BB	128318-3X3	281	See Legend	V-hook	120-277	4000	42,515	151	80	50,000	-4 to 122
G2ELHB-4-281-SV-XXX-50-D-BB	128318-3X5	281	See Legend	V-hook	120-277	5000	43,077	153	80	50,000	-4 to 122
4-ft 281W G2 Eco Linear High Bay, Standard Voltage, Integrated Microwave Sensor, 16W Battery Backup											
G2ELHB-4-281-SV-XXX-30-D-IS-BB	128328-3X1	281	See Legend	V-hook	120-277	3000	40,267	143	80	50,000	-4 to 122
G2ELHB-4-281-SV-XXX-40-D-IS-BB	128328-3X3	281	See Legend	V-hook	120-277	4000	42,515	151	80	50,000	-4 to 122
G2ELHB-4-281-SV-XXX-50-D-IS-BB	128328-3X5	281	See Legend	V-hook	120-277	5000	43,077	153	80	50,000	-4 to 122
4-ft 321W G2 Eco Linear High Bay, Standard Voltage											
G2ELHB-4-321-SV-XXX-30-D	128019-3X1	321	See Legend	V-hook	120-277	3000	45,870	142	80	50,000	-4 to 131
G2ELHB-4-321-SV-XXX-40-D	128019-3X3	321	See Legend	V-hook	120-277	4000	47,957	149	80	50,000	-4 to 131
G2ELHB-4-321-SV-XXX-50-D	128019-3X5	321	See Legend	V-hook	120-277	5000	48,567	151	80	50,000	-4 to 131
4-ft 321W G2 Eco Linear High Bay, Standard Voltage, Integrated Microwave Sensor											
G2ELHB-4-321-SV-XXX-30-D-IS	128029-3X1	321	See Legend	V-hook	120-277	3000	45,870	142	80	50,000	-4 to 131
G2ELHB-4-321-SV-XXX-40-D-IS	128029-3X3	321	See Legend	V-hook	120-277	4000	47,957	149	80	50,000	-4 to 131
G2ELHB-4-321-SV-XXX-50-D-IS	128029-3X5	321	See Legend	V-hook	120-277	5000	48,567	151	80	50,000	-4 to 131
4-ft 321W G2 Eco Linear High Bay, Standard Voltage, 16W Battery Backup											
G2ELHB-4-321-SV-XXX-30-D-BB	128319-3X1	321	See Legend	V-hook	120-277	3000	45,870	142	80	50,000	-4 to 122
G2ELHB-4-321-SV-XXX-40-D-BB	128319-3X3	321	See Legend	V-hook	120-277	4000	47,957	149	80	50,000	-4 to 122
G2ELHB-4-321-SV-XXX-50-D-BB	128319-3X5	321	See Legend	V-hook	120-277	5000	48,567	151	80	50,000	-4 to 122
4-ft 321W G2 Eco Linear High Bay, Standard Voltage, Integrated Microwave Sensor, 16W Battery Backup											
G2ELHB-4-321-SV-XXX-30-D-IS-BB	128329-3X1	321	See Legend	V-hook	120-277	3000	45,870	142	80	50,000	-4 to 122
G2ELHB-4-321-SV-XXX-40-D-IS-BB	128329-3X3	321	See Legend	V-hook	120-277	4000	47,957	149	80	50,000	-4 to 122
G2ELHB-4-321-SV-XXX-50-D-IS-BB	128329-3X5	321	See Legend	V-hook	120-277	5000	48,567	151	80	50,000	-4 to 122
4-ft 481W G2 Eco Linear High Bay, Standard Voltage											
G2ELHB-4-481-SV-XXX-30-D	12801A-3X1	481	See Legend	V-hook	120-277	3000	68,831	143	80	50,000	-4 to 131
G2ELHB-4-481-SV-XXX-40-D	12801A-3X3	481	See Legend	V-hook	120-277	4000	72,005	149	80	50,000	-4 to 131
G2ELHB-4-481-SV-XXX-50-D	12801A-3X5	481	See Legend	V-hook	120-277	5000	73,015	151	80	50,000	-4 to 131
4-ft 481W G2 Eco Linear High Bay, Standard Voltage, Integrated Microwave Sensor											
G2ELHB-4-481-SV-XXX-30-D-IS	12802A-3X1	481	See Legend	V-hook	120-277	3000	68,831	143	80	50,000	-4 to 131
G2ELHB-4-481-SV-XXX-40-D-IS	12802A-3X3	481	See Legend	V-hook	120-277	4000	72,005	149	80	50,000	-4 to 131
G2ELHB-4-481-SV-XXX-50-D-IS	12802A-3X5	481	See Legend	V-hook	120-277	5000	73,015	151	80	50,000	-4 to 131
4-ft 481W G2 Eco Linear High Bay, Standard Voltage, 16W Battery Backup											
G2ELHB-4-481-SV-XXX-30-D-BB	12831A-3X1	481	See Legend	V-hook	120-277	3000	68,831	143	80	50,000	-4 to 122
G2ELHB-4-481-SV-XXX-40-D-BB	12831A-3X3	481	See Legend	V-hook	120-277	4000	72,005	149	80	50,000	-4 to 122
G2ELHB-4-481-SV-XXX-50-D-BB	12831A-3X5	481	See Legend	V-hook	120-277	5000	73,015	151	80	50,000	-4 to 122
4-ft 481W G2 Eco Linear High Bay, Standard Voltage, Integrated Microwave Sensor, 16W Battery Backup											
G2ELHB-4-481-SV-XXX-30-D-IS-BB	12832A-3X1	481	See Legend	V-hook	120-277	3000	68,831	143	80	50,000	-4 to 122
G2ELHB-4-481-SV-XXX-40-D-IS-BB	12832A-3X3	481	See Legend	V-hook	120-277	4000	72,005	149	80	50,000	-4 to 122
G2ELHB-4-481-SV-XXX-50-D-IS-BB	12832A-3X5	481	See Legend	V-hook	120-277	5000	73,015	151	80	50,000	-4 to 122

Product is DLC-listed, Premium.

TECHNICAL DATA - LENS OPTIONS LEGEND


Use the following table to choose and determine the final SKU number to use when submitting orders.

For example, if you need the 90° Medium Discrete Lens, use "0" in place of "X". So that means that the final SKU to reference on an order form for an 81W standard voltage linear high bay in 4000K would be "128011-303".

Lens Type	Catalog No. Variable	SKU Variable
Discrete Lens Medium (90°)	XXX = DLM	X = 0
Discrete Lens Aisle (45°)	XXX = DLA	X = 2
General Lens Frosted (110°)	XXX = GLF	X = 1

Specification Sheet: G2 Eco Linear High Bays

OPTIONAL ACCESSORIES




Wire Guard Kits
(SKUs: 12800W-301 (55W, 81W, and 101W);
12800W-302 (141W, 161W, and 201W 2-ft);
12800W-303 (141W and 201W 4-ft);
12800W-304 (281W and 321W);
12800W-305 (481W))



Passive Infrared Accessory Motion Sensor Kit
SKU: 12800P-302 (120-277VAC Only)



Remote Control for Integrated and Accessory
Sensors
SKU: 12800P-305



Pendant-Mounting Bracket Kit
SKU: 12800M-301



12-ft Aircraft Cable Hanging Kit (Pair)
SKU: 12800M-303



10KA Surge Protector
(Factory Installed Accessory)
SKU: 12800S-301 (120-277VAC Only)

PHYSICAL DATA (Representative standard voltage examples shown.)

Catalog No.	Product SKU No.	Product Dimensions (in.)	Product Weight (lb.)
2-ft 55W Contractor-Grade Linear High Bay, Standard Voltage			
G2ELHB-2-55-SV-DLM-40-D	128010-303	14.7W x 25.5L x 2.1H	7.5
2-ft 81W Contractor-Grade Linear High Bay, Standard Voltage			
G2ELHB-2-81-SV-DLM-40-D	128011-303	14.7W x 25.5L x 2.1H	7.9
2-ft 101W Contractor-Grade Linear High Bay, Standard Voltage			
G2ELHB-2-101-SV-DLM-40-D	128012-303	14.7W x 25.5L x 2.1H	7.9
2-ft 141W Contractor-Grade Linear High Bay, Standard Voltage			
G2ELHB-2-141-SV-DLM-40-D	128013-303	18.1W x 25.5L x 2.1H	11.9
2-ft 161W Contractor-Grade Linear High Bay, Standard Voltage			
G2ELHB-2-161-SV-DLM-40-D	128015-303	18.1W x 25.5L x 2.1H	12.8
2-ft 201W Contractor-Grade Linear High Bay, Standard Voltage			
G2ELHB-2-201-SV-DLM-40-D	128016-303	18.1W x 25.5L x 2.1H	12.8
4-ft 141W Contractor-Grade Linear High Bay, Standard Voltage			
G2ELHB-4-141-SV-DLM-40-D	128014-303	14.7W x 48.8L x 2.1H	14.8
4-ft 201W Contractor-Grade Linear High Bay, Standard Voltage			
G2ELHB-4-201-SV-DLM-40-D	128017-303	14.7W x 48.8L x 2.1H	15.7
4-ft 281W Contractor-Grade Linear High Bay, Standard Voltage			
G2ELHB-4-281-SV-DLM-40-D	128018-303	18.1W x 48.8L x 2.1H	19.2
4-ft 321W Contractor-Grade Linear High Bay, Standard Voltage			
G2ELHB-4-321-SV-DLM-40-D	128019-303	18.1W x 48.8L x 2.1H	20.9
4-ft 481W Contractor-Grade Linear High Bay, Standard Voltage			
G2ELHB-4-481-SV-DLM-40-D	12801A-303	24.0W x 48.8L x 2.1H	28.2

Specification Sheet: G2 Eco Linear High Bays

PHYSICAL DATA

Catalog No.	Product SKU No.	Product Dimensions (in.)	Product Weight (lb)	Product Dimensions with Battery (in.)	Product Weight with Battery (lb)
Standard-Voltage Eco Linear High Bays (120-277VAC)					
64W 1' x 2' Eco Linear High Bay					
ELHB-64-12-D-XXX-SV-40	128010-1X3	24L x 14W x 2.88H	8.8	24L x 14W x 6H	13.3
ELHB-64-12-D-XXX-SV-50	128010-1X5	24L x 14W x 2.88H	8.8	24L x 14W x 6H	13.3
83W 1' x 2' Eco Linear High Bay					
ELHB-83-12-D-XXX-SV-40	128011-1X3	24L x 14W x 2.88H	8.8	24L x 14W x 6H	13.3
ELHB-83-12-D-XXX-SV-50	128011-1X5	24L x 14W x 2.88H	8.8	24L x 14W x 6H	13.3
100W 2' x 2' Eco Linear High Bay					
ELHB-100-22-D-XXX-SV-40	128016-1X3	24L x 24W x 2.88H	14	24L x 24W x 6H	18.5
ELHB-100-22-D-XXX-SV-50	128016-1X5	24L x 24W x 2.88H	14	24L x 24W x 6H	18.5
128W 2' x 2' Eco Linear High Bay					
ELHB-128-22-D-XXX-SV-40	128012-1X3	24L x 24W x 2.88H	14	24L x 24W x 6H	18.5
ELHB-128-22-D-XXX-SV-50	128012-1X5	24L x 24W x 2.88H	14	24L x 24W x 6H	18.5
167W 2' x 2' Eco Linear High Bay					
ELHB-167-22-D-XXX-SV-40	128013-1X3	24L x 24W x 2.88H	14	24L x 24W x 6H	18.5
ELHB-167-22-D-XXX-SV-50	128013-1X5	24L x 24W x 2.88H	14	24L x 24W x 6H	18.5
160W 2' x 4' Eco Linear High Bay					
ELHB-160-24-D-XXX-SV-40	128017-1X3	48L x 24W x 2.88H	24.4	48L x 24W x 6H	28.9
ELHB-160-24-D-XXX-SV-50	128017-1X5	48L x 24W x 2.88H	24.4	48L x 24W x 6H	28.9
258W 2' x 4' Eco Linear High Bay					
ELHB-258-24-D-XXX-SV-40	128014-1X3	48L x 24W x 2.88H	24.4	48L x 24W x 6H	28.9
ELHB-258-24-D-XXX-SV-50	128014-1X5	48L x 24W x 2.88H	24.4	48L x 24W x 6H	28.9
High-Voltage Eco Linear High Bays (347VAC/480VAC)					
70W 1' x 2' Eco Linear High Bay					
ELHB-70-12-D-XXX-HV-40	128210-1X3	24L x 14W x 2.88H	11	24L x 14W x 6H	15.5
ELHB-70-12-D-XXX-HV-50	128210-1X5	24L x 14W x 2.88H	11	24L x 14W x 6H	15.5
91W 1' x 2' Eco Linear High Bay					
ELHB-91-12-D-XXX-HV-40	128211-1X3	24L x 14W x 2.88H	11	24L x 14W x 6H	15.5
ELHB-91-12-D-XXX-HV-50	128211-1X5	24L x 14W x 2.88H	11	24L x 14W x 6H	15.5
140W 2' x 2' Eco Linear High Bay					
ELHB-140-22-D-XXX-HV-40	128212-1X3	24L x 24W x 2.88H	16.5	24L x 24W x 6H	21
ELHB-140-22-D-XXX-HV-50	128212-1X5	24L x 24W x 2.88H	16.5	24L x 24W x 6H	21
182W 2' x 2' Eco Linear High Bay					
ELHB-182-22-D-XXX-HV-40	128213-1X3	24L x 24W x 2.88H	16.5	24L x 24W x 6H	21
ELHB-182-22-D-XXX-HV-50	128213-1X5	24L x 24W x 2.88H	16.5	24L x 24W x 6H	21
282W 2' x 4' Eco Linear High Bay					
ELHB-282-24-D-XXX-HV-40	128214-1X3	48L x 24W x 2.88H	29.7	48L x 24W x 6H	34.2
ELHB-282-24-D-XXX-HV-50	128214-1X5	48L x 24W x 2.88H	29.7	48L x 24W x 6H	34.2
365W 2' x 4' Eco Linear High Bay					
ELHB-365-24-D-XXX-HV-40	128215-1X3	48L x 24W x 2.88H	29.7	48L x 24W x 6H	34.2
ELHB-365-24-D-XXX-HV-50	128215-1X5	48L x 24W x 2.88H	29.7	48L x 24W x 6H	34.2

Note: Physical dimensions and weights will vary, depending on which optional accessories are ordered.