

# Specification Sheet: G4 Wall Pack

## The Energy Efficient LED Solution

Whether you need to light your building exterior in complimentary light to show it at its best, or provide security around it, our LED wall packs deliver energy-saving options of 0-10V dimming and a dusk-to-dawn photocell, combined with a 70,000-hour rated life and 10-year warranty to ensure safety through high-quality lighting. Our state-of-the-art LED lighting solutions are durable, reliable and high-performance. Ideal for either dry or wet locations, our G4 Wall Pack features an IP65-rated, bronze-colored aluminum housing.

### APPLICATIONS


- Walkways
- Building Perimeters
- Security Areas
- Parking Structures
- Egress Illumination

### BEAM ANGLE



Revolution Lighting Light Distribution

### CAN DECREASE ENERGY USAGE BY



vs. Similar Fluorescent Lamps

### WARRANTY



Our Industry-Leading 10-Year Limited Warranty Guarantees Unsurpassed Quality

## PRODUCT BENEFITS

### OPERATIONAL

- 3X greater lamp life than fluorescent
- 70,000-hour rated lifetime reduces long-term maintenance costs
- Instant on, no warm-up time
- High-voltage option available (347-480VAC)
- Button photocell (dusk-to-dawn sensor) included
- 0-10V dimming

### SAFETY

- Negligible light depreciation over time
- Superior light output
- IP65

### SUSTAINABILITY

- Lack of UV or IR minimizes concerns with fading or discoloration
- Mercury-free, allowing for non-hazardous disposal
- 100% recyclable



## ORDER LOGIC (Ex. G4WP-30-SV-BZ-40-D-P)

Product Description	Wattage	Input Voltage (VAC)	Housing Color	CCT (K Temp)	Dimming Option	Photocell
	30 = 30W			40 = 4000		
G4WP = G4 Wall Pack	- 40 = 40W	- SV = 120-277VAC	- BZ = Bronze	- 40 = 4000 50 = 5000	- D = 0-10V Dimming	- P = Button Photocell
	60 = 60W			40 = 4000		



# Specification Sheet: G4 Wall Pack

## TECHNICAL DATA (Subject to change.)

Catalog No.	Product SKU No.	Rated Watts	Input Voltage (VAC)	Color Temp (K)	Rated Lumens	Rated Efficacy (lm/W)	CRI	Beam Angle	Rated Life (Hours)	Operating Temp. (°F)
<b>30W G4 Wall Pack with Button Photocell</b>										
G4WP-30-SV-BZ-40-D-P	284100-203	27.6	120-277	4000	3,557	128	81	80 x 100	70,000	-4 to 113
<b>40W G4 Wall Pack with Button Photocell</b>										
G4WP-40-SV-BZ-40-D-P	284102-203	40.7	120-277	4000	5,471	134	80	80 x 100	70,000	-4 to 113
G4WP-40-SV-BZ-50-D-P	284102-205	40.8	120-277	5000	5,645	138	81	80 x 100	70,000	-4 to 113
<b>60W G4 Wall Pack with Button Photocell</b>										
G4WP-60-SV-BZ-40-D-P	284104-203	59.5	120-277	4000	8,055	135	80	80 x 100	70,000	-4 to 113

Product is DLC-Premium

## PHYSICAL DATA

Catalog No.	Product SKU No.	Product Dimensions (in.)	Product Weight (lb)
<b>30W G4 Wall Pack with Button Photocell</b>			
G4WP-30-SV-BZ-40-D-P	284100-203	10.62W x 7.59L x 6.61H	6.0
<b>40W G4 Wall Pack with Button Photocell</b>			
G4WP-40-SV-BZ-40-D-P	284102-203	14.6W x 9.48L x 7.72H	9.6
G4WP-40-SV-BZ-50-D-P	284102-205	14.6W x 9.48L x 7.72H	9.6
<b>60W G4 Wall Pack with Button Photocell</b>			
G4WP-60-SV-BZ-40-D-P	284104-203	14.6W x 9.48L x 7.72H	9.6