

Specification Sheet: Uni-Fit G2 T5 LED Tubes

Retrofitting Is Easy with Our Energy Efficient Led Tubes

Our lightweight, shatterproof, all-plastic T5 Uni-Fit LED tubes can reduce your lighting energy use by as much as 40% compared to fluorescent lights and provide a superior quality of light.

Our plug-n-play tubes are ballast ready for easy installation without rewiring and are backed with our industry-leading 70,000 hour lamp life and 10-year warranty.

APPLICATIONS


- Offices & Commercial Buildings
- Retail Settings
- Hotels
- Schools
- Hospitals
- Warehouses
- Assisted Living Facilities
- Food Processing Centers
- Parking Garages
- Recreation Centers

ILLUMINATION ANGLE



Revolution Lighting Light Distribution

CAN DECREASE ENERGY USAGE BY



vs. Similar Fluorescent Lamps

WARRANTY



Our Industry-Leading 10-Year Limited Warranty Guarantees Unsurpassed Quality

PRODUCT BENEFITS

OPERATIONAL

- 3X greater lamp life than fluorescent, supported by industry-leading 10-year warranty
- 70,000-hour lamp life reduces long-term maintenance costs
- Instant on, no warm-up time

SAFETY

- No glass
- Negligible light depreciation over time
- Superior light output
- UL Type A tube lamps are tested to comply with UL 1993

SUSTAINABILITY

- Lack of UV or IR minimizes concerns with fading or discoloration
- Mercury-free, allowing for non-hazardous disposal
- 100% recyclable



ORDER LOGIC (Ex. UF2-46-27-F-HO-35)

Product Description	Length (in.)	Bare Lamp Wattage	Lens	Output	CCT (K Temp)
UF2 = Uni-Fit, G2 (Ballast-Ready)	46 = 45.25 in.	27 14	F = Frosted	HO = High Output HE = High Efficiency	30 = 3000K 35 = 3500K 40 = 4000K 50 = 5000K



Specification Sheet: Uni-Fit G2 T5 LED Tubes

TECHNICAL DATA (Subject to change.)*

Catalog No.	Product SKU No.	Rated Wattage	Lens	Base	Input Voltage	Color Temp (K)	Rated Lumens	Rated Efficacy	CRI	Illumination Angle	Rated Life (Hours)	Operating Temp. (°F)	NSF Listed
G2 Uni-Fit 27W T5 HO Tube													
UF2-46-27-F-HO-30	204321-210	31.7	Frosted	G5	T5 Ballast	3000	3,354	106	84	310	70,000	-4 to 122	•
UF2-46-27-F-HO-35	204321-211	31.7	Frosted	G5	T5 Ballast	3500	3,419	108	84	310	70,000	-4 to 122	•
UF2-46-27-F-HO-40	204321-212	31.7	Frosted	G5	T5 Ballast	4000	3,485	110	84	310	70,000	-4 to 122	•
UF2-46-27-F-HO-50	204321-213	31.7	Frosted	G5	T5 Ballast	5000	3,615	114	83	310	70,000	-4 to 122	•
G2 Uni-Fit 14W T5 HE Tube													
UF2-46-14-F-HE-30	204320-210	14	Frosted	G5	T5 Ballast	3000	1,900	136	80	310	70,000	-4 to 122	•
UF2-46-14-F-HE-35	204320-211	14	Frosted	G5	T5 Ballast	3500	1,925	138	80	310	70,000	-4 to 122	•
UF2-46-14-F-HE-40	204320-212	14	Frosted	G5	T5 Ballast	4000	1,950	139	80	310	70,000	-4 to 122	•
UF2-46-14-F-HE-50	204320-213	14	Frosted	G5	T5 Ballast	5000	2,000	143	80	310	70,000	-4 to 122	•

Product is DLC listed.

* NOTE: The above rated performance specs were obtained with standard T5 HO/HE ballasts having a ballast factor of 1.0. Ballast-performance information is provided for reference only. Actual performance will vary.

PHYSICAL DATA

Catalog No.	Product SKU No.	Product Dimensions (in.)	Product Weight (lb)
G2 Uni-Fit 27W T5 HO Tube			
UF2-46-27-F-HO-30	204321-210	45.8L x 0.71 Dia.	0.35
UF2-46-27-F-HO-35	204321-211	45.8L x 0.71 Dia.	0.35
UF2-46-27-F-HO-40	204321-212	45.8L x 0.71 Dia.	0.35
UF2-46-27-F-HO-50	204321-213	45.8L x 0.71 Dia.	0.35
G2 Uni-Fit 14W T5 HE Tube			
UF2-46-14-F-HE-30	204320-210	45.8L x 0.71 Dia.	0.35
UF2-46-14-F-HE-35	204320-211	45.8L x 0.71 Dia.	0.35
UF2-46-14-F-HE-40	204320-212	45.8L x 0.71 Dia.	0.35
UF2-46-14-F-HE-50	204320-213	45.8L x 0.71 Dia.	0.35