

# Specification Sheet: Vapor-Tight LED

## Uniform High-Visibility for Added Security

Our state-of-the-art, energy efficient Vapor Tight LED fixtures provide superior lighting for parking garages, warehouses, industrial facilities and food processing centers, while reducing operating and maintenance costs.

With custom-designed low-glare optics, these fixtures have been specifically designed to provide superior uniformity for high visibility and added security. Ideal for wet or harsh interior/exterior environments, the shock- and vibration-resistant fixtures are UL-listed, for either wall- or ceiling-mounted installations and feature a tamper-proof housing.

### APPLICATIONS


- Food Processing Facilities
- Warehouses
- Parking Garages
- Wet Environments
- Walkway Canopies
- Harsh Environments
- Hospitals
- School Gymnasiums
- Recreation Centers

### ILLUMINATION ANGLE



Revolution Lighting Light Distribution

### CAN DECREASE ENERGY USAGE BY



vs. Similar Fluorescent Lamps

### WARRANTY



Our Industry-Leading 7-Year Limited Warranty Guarantees Unsurpassed Quality

## PRODUCT BENEFITS

### OPERATIONAL

- 3X greater lamp life than fluorescent, supported by industry-leading 7-year warranty
- 50,000-hour lamp life reduces long-term maintenance costs
- Sealed, vapor-tight, water-resistant, IP66 fixture

### SAFETY

- High shock resistance
- Negligible light depreciation over time
- Superior light output
- Tamper-proof housing

### SUSTAINABILITY

- Lack of UV or IR minimizes concerns with fading or discoloration
- Mercury-free, allowing for non-hazardous disposal



## ORDER LOGIC (Ex. VT-12S-30-FPC-40-TP)

Product Description	Dimensions	Wattage	Lens	CCT (K Temp)	Option
VT = Vapor-Tight	12S = 1x2, Slim	30 = 30W	FPC = Frosted Polycarbonate	40 = 4000	TP = Tamper-Proof
VT = Vapor-Tight	14S = 1x4, Slim	40 = 40W 50 = 50W		40 = 4000 50 = 5000	



# Specification Sheet: Vapor-Tight LED

## TECHNICAL DATA (Subject to change)

Catalog No.	Product SKU No.	Rated Watts	Lens	Mounting	Input Voltage (VAC)	Color Temp (K)	Rated Lumens	Rated Efficacy (lm/W)	CRI	Illumination Angle	Rated Life (Hours)	Operating Temp. (°F)
<b>1x2 Tamper-Proof Vapor-Tight</b>												
VT-12S-30-FPC-40-TP	114201-101	30	Frosted	Hanging/Surface Mount	120-277	4000	2,900	100	80	260	50,000	-4 to 113
<b>1x4 Tamper-Proof Vapor-Tight</b>												
VT-14S-40-FPC-40-TP	114402-101	40	Frosted	Hanging/Surface Mount	120-277	4000	4,100	100	80	260	50,000	-4 to 113
VT-14S-40-FPC-50-TP	114402-102	40	Frosted	Hanging/Surface Mount	120-277	5000	4,100	100	80	260	50,000	-4 to 113
VT-14S-50-FPC-40-TP	114403-101	50	Frosted	Hanging/Surface Mount	120-277	4000	5,100	100	80	260	50,000	-4 to 113
VT-14S-50-FPC-50-TP	114403-102	50	Frosted	Hanging/Surface Mount	120-277	5000	5,100	100	80	260	50,000	-4 to 113

Product is DLC listed.

## PHYSICAL DATA

Catalog No.	Product SKU No.	Product Dimensions (in)	Product Weight (lb)
<b>1x2 Slim Tamper-Proof Vapor-Tight</b>			
VT-12S-30-FPC-40-TP	114201-101	24.0L x 3.8W x 2.8H	3.3
<b>1x4 Slim Tamper-Proof Vapor-Tight</b>			
VT-14S-40-FPC-40-TP	114402-101	47.8L x 3.8W x 2.8H	5.5
VT-14S-40-FPC-50-TP	114402-102	47.8L x 3.8W x 2.8H	5.5
VT-14S-50-FPC-40-TP	114403-101	47.8L x 3.8W x 2.8H	5.5
VT-14S-50-FPC-50-TP	114403-102	47.8L x 3.8W x 2.8H	5.5