

Specification Sheet: Uni-Fit T8 LED Tubes

Retrofitting Is Easy with Our Energy Efficient LED Tubes

Our lightweight, shatterproof, all-plastic T8 Uni-Fit LED tubes can reduce your lighting energy use by as much as 55% compared to fluorescent lights and provide a superior quality of light.

Our tubes are ballast-ready for easy installation without rewiring and are backed with our industry-leading 70,000-hour rated lamp life and 10-year warranty.

See Order Logic table below for our BAA compliant products. Contact your Revolution Lighting representative for pricing or more information.

APPLICATIONS


- Offices & Commercial Buildings
- Retail Settings
- Hotels
- Schools
- Hospitals
- Warehouses
- Assisted Living Facilities
- Food Processing Centers
- Parking Garages
- Recreation Centers

ILLUMINATION ANGLE



Revolution Lighting Light Distribution

CAN DECREASE ENERGY USAGE BY



vs. Similar Fluorescent Lamps

WARRANTY



Our Industry-Leading 10-Year Limited Warranty Guarantees Unsurpassed Quality

PRODUCT BENEFITS

OPERATIONAL

- 3X greater lamp life than fluorescent, supported by industry-leading 10-year warranty
- 70,000 hour lamp life reduces long-term maintenance costs
- Instant on, no warm-up time

SAFETY

- No glass
- Negligible light depreciation over time
- Superior light output
- These UL Type A tube lamps are tested to comply with UL 1993

SUSTAINABILITY

- Lack of UV or IR minimizes concerns with fading or discoloration
- Mercury-free, allowing for non-hazardous disposal
- 100% recyclable



ORDER LOGIC (Ex. UF-36-9-F-35-USA or UF-36-9-F-35)

Product Description	Length (in.)	Bare Lamp Wattage	Lens	CCT (K Temp)	BAA
UF = Uni-Fit (Ballast-Ready)	24 = 2ft	7.5 = 7.5W		30 = 3000K	Blank = Standard (non-BAA) USA = BAA (Buy American Act) A = TAA (Trade Agreements Act)
UF = Uni-Fit (Ballast-Ready)	36 = 3ft	9 = 9W		35 = 3500K	
UF = Uni-Fit (Ballast-Ready)	48 = 4ft	12 = 12W	F = Frosted	40 = 4000K	
		14 = 14W		50 = 5000K	
		17 = 17W			
UF = Uni-Fit (Ballast-Ready)	U = U-Bent	18 = 18W		30 = 3000K 35 = 3500K 40 = 4000K 50 = 5000K	(Not available with BAA at this time.)



Specification Sheet: Uni-Fit T8 LED Tubes

TECHNICAL DATA (Subject to change)

Catalog No.	Product SKU No.	BAA/TAA Option*	Rated System Wattage	Lens	Base	Input Voltage	Color Temp (K)	Rated Lumens	Rated Efficacy	CRI	Illumination Angle	Rated Life (Hours)	Operating Temp. (°F)	NSF Listed
2-foot 7.5W Uni-Fit Tube														
UF-24-7.5-F-35	202220-012	Yes	9	Frosted	G13	Ballast	3500	1,500	167	80	320	70,000	-4 to 122	
UF-24-7.5-F-40	202220-013	Yes	9	Frosted	G13	Ballast	4000	1,500	167	80	320	70,000	-4 to 122	
UF-24-7.5-F-50	202220-015	Yes	9	Frosted	G13	Ballast	5000	1,500	167	80	320	70,000	-4 to 122	
3-foot 9W Uni-Fit Tube														
UF-36-9-F-35	203220-012	Yes	14.3	Frosted	G13	Ballast	3500	1,621	114	84	320	70,000	-4 to 122	
UF-36-9-F-40	203220-013	Yes	14.3	Frosted	G13	Ballast	4000	1,615	113	82	320	70,000	-4 to 122	
UF-36-9-F-50	203220-015	Yes	14.3	Frosted	G13	Ballast	5000	1,672	117	83	320	70,000	-4 to 122	
4-foot G2 12W Uni-Fit Tube														
UF-48-12-F-30	204220-011	Yes	15.6	Frosted	G13	Ballast	3000	1,745	111	83	320	70,000	-4 to 122	•
UF-48-12-F-35	204220-012	Yes	13.9	Frosted	G13	Ballast	3500	1,759	127	83	320	70,000	-4 to 122	
UF-48-12-F-40	204220-013	Yes	13.9	Frosted	G13	Ballast	4000	1,646	119	85	320	70,000	-4 to 122	•
UF-48-12-F-50	204220-015	Yes	13.9	Frosted	G13	Ballast	5000	1,687	122	85	320	70,000	-4 to 122	•
4-foot G2 14W Uni-Fit Tube														
UF-48-14-F-35	204221-012	Yes	15.6	Frosted	G13	Ballast	3500	1,735	111	82	310	70,000	-4 to 122	
UF-48-14-F-40	204221-013	Yes	15.6	Frosted	G13	Ballast	4000	1,971	126	83	310	70,000	-4 to 122	•
UF-48-14-F-50	204221-015	Yes	15.3	Frosted	G13	Ballast	5000	1,792	117	86	310	70,000	-4 to 122	•
4-foot G2 17W Uni-Fit Tube														
UF-48-17-F-35	204222-012	Yes	17.8	Frosted	G13	Ballast	3500	1,926	108	82	310	70,000	-4 to 122	
UF-48-17-F-40	204222-013	Yes	17.6	Frosted	G13	Ballast	4000	2,110	120	86	310	70,000	-4 to 122	•
U-Bent 18W Uni-Fit Tube														
UF-U-18-F-30	207221-211	No	18.4	Frosted	G13	Ballast	3000	2,227	121	81	276	50,000	-4 to 113	•
UF-U-18-F-35	207221-212	No	18.4	Frosted	G13	Ballast	3500	2,247	122	81	276	50,000	-4 to 113	•
UF-U-18-F-40	207221-213	No	18.4	Frosted	G13	Ballast	4000	2,267	123	81	276	50,000	-4 to 113	•
UF-U-18-F-50	207221-215	No	18.5	Frosted	G13	Ballast	5000	2,306	124	85	276	50,000	-4 to 113	•

Product is DLC listed.

*Note: When ordering BAA- or TAA-compliant tubes, include the extension "-USA" or "-A" after the SKU No., respectively, as shown in the Order Logic table.

Specification Sheet: Uni-Fit T8 LED Tubes

PHYSICAL DATA

Catalog No.	Product SKU No.	Product Dimensions (in.)	Product Weight (lb)
2-foot 9W Uni-Fit Tube			
UF-24-7.5-F-35	202220-012	24L x 1 Dia.	0.22
UF-24-7.5-F-40	202220-013	24L x 1 Dia.	0.22
UF-24-7.5-F-50	202220-015	24L x 1 Dia.	0.22
3-foot 9W Uni-Fit Tube			
UF-36-9-F-35	203220-012	36L x 1 Dia.	0.30
UF-36-9-F-40	203220-013	36L x 1 Dia.	0.30
UF-36-9-F-50	203220-015	36L x 1 Dia.	0.30
4-foot G2 12W Uni-Fit Tube			
UF-48-12-F-30	204220-011	48L x 1 Dia.	0.38
UF-48-12-F-35	204220-012	48L x 1 Dia.	0.38
UF-48-12-F-40	204220-013	48L x 1 Dia.	0.38
UF-48-12-F-50	204220-015	48L x 1 Dia.	0.38
4-foot G2 14W Uni-Fit Tube			
UF-48-14-F-35	204221-012	48L x 1 Dia.	0.54
UF-48-14-F-40	204221-013	48L x 1 Dia.	0.54
UF-48-14-F-50	204221-015	48L x 1 Dia.	0.54
4-foot G2 17W Uni-Fit Tube			
UF-48-17-F-35	204222-012	48L x 1 Dia.	0.54
UF-48-17-F-40	204222-013	48L x 1 Dia.	0.54
U-Bent 18W Uni-Fit Tube			
UF-U-18-F-30	207221-211	22.50L x 7.13W x 1.00H	0.52
UF-U-18-F-35	207221-212	22.50L x 7.13W x 1.00H	0.52
UF-U-18-F-40	207221-213	22.50L x 7.13W x 1.00H	0.52
UF-U-18-F-50	207221-215	22.50L x 7.13W x 1.00H	0.52